

BGF.1M.100.XAV

SUMMARY

Wires

Low



Image is for illustrative purpose only

		100
High	0	
Coax	0	
Triax	0	Download
Quad	0	Request a quote
Fiber	0	Catalog
Fluidic	0	
Series	1M	
Termination type	No contacts / Accessory	
IP rating	50	
Cable Ø	0.00 - 0.00 mm	
Matching parts		
Status	active	

TECHNICAL DETAILS

0

Mechanics

Alternative part

Shell Style/Model	BGF*: Blanking cap for plugs (arctic grip)
Keying	
Housing Material	Environment friendly aluminium (nickel plated, anthracite color) shell and nut, other pieces bronze/brass
Cable Fixing	: 0 - 0 mm
Variant	

Performance

Configuration Insulator Rated Current


Others

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Operating temperature: -55°C/ +200°C Climatical Category: 15/200/21 (Al. shell) Lighting strike EIA 364-75 10K amps - 6 times EMI Shielding EIA 364-66A - 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB IP Rating: 50

DRAWINGS

Draws



Dimensions

	А	С	L	Ν	Р	Х
mm.	15.9	14.2	24.6	85	5.3	6
in.	0,63	0,56	0,97	3,35	0,21	0,24

RECOMMENDED BY LEMO

Tools

None

Cables

121 221		
131 221		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

151 221		
161 221		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.