



# EGN.2M.310.XLM

## MECHANICAL DETAILS

**Shell Style Model** EG\* : Fixed receptacle nut fixing

**Keying** 3 keys (beta=165, gamma=30, plug: male contacts, receptacle: female contacts)

**Housing Material** Environment friendly aluminium (nickel plated, anthracite color) shell and nut, other pieces bronze/brass

**Cable Fixing** 0 - 0 mm

**Variant 2** :

	C	D	E	L	P	S1	e
Mm.	17.2	6.8	4.5	18.1	5.3	12.5	M14x1.0
In.	0.68	0.27	0.18	0.71	0.21	0.49	

## PERFORMANCE DETAIL

**Insert** 2M.310 : 10 Low Voltage

**Insulator**

**Specifications**

**Contact Type:** Crimp

**Max. Matings:** 5000

**Contact** 30 N

**Contact Dia.:** 0.9 mm (0.035in)

**Bucket Dia.:** 1.1 mm (0.043in)

**Min. Conductor:** 0.25 mm<sup>2</sup> (AWG 24)

**Max. Conductor:** 0.5 mm<sup>2</sup> (AWG 20)

**R (max):** 4.8 mOhm

**Extractor:** DCF.93.090.4LT

**Positioner:** DCE.91.090.3MM

## OTHER CHARACTERISTICS

**Shell Style/Model** Libellé

**Humidity (max):** <=95% [at 60 deg C /140 F]

**Vibration:** 15 g [10 Hz - 2000 Hz]

**Shock Resistance:** 100 g [ 6 ms]

**Operating** -55°C / +200°C

**Climatical** 15/200/21 (Al. shell)

**Lighting strike EIA** 10K amps - 6 times

**EMI Shielding EIA** - 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB

**IP Rating** 68

