



# EGN.3M.330.XLM

## MECHANICAL DETAILS

**Shell Style Model** EG\* : Fixed receptacle  
nut fixing


**Keying**

**Housing Material** Environment friendly aluminium  
(nickel plated, anthracite color)  
shell and nut, other pieces  
bronze/brass

**Cable Fixing** 0 - 0 mm

**Variant 2** :

	Col	Col	Col	Col	Col	Col	Col	Col
Mm.								
In.								



## PERFORMANCE DETAIL

**Insert** 3M.330 : 30 Low Voltage

**Insulator**

**Specifications**

**Contact Type:** Crimp

**Max. Matings:** 5000

**Contact** 22 N

**Contact Dia.:** 0.7 mm (0.028in)

**Bucket Dia.:** 0.8 mm (0.031in)

**Min. Conductor:** 0.14 mm<sup>2</sup> (AWG 26)

**Max. Conductor:** 0.34 mm<sup>2</sup> (AWG 22)

**R (max):** 6.1 mOhm

**Positioner:** DCE.91.070.3MM

## OTHER CHARACTERISTICS

**Shell Style/Model** Libellé

**Humidity (max):** <=95% [at 60 deg C /140 F]

**Vibration:** 15 g [10 Hz - 2000 Hz]

**Shock Resistance:** 100 g [ 6 ms]

**Operating** -55°C/ +200°C

**Climatical** 15/200/21 (Al. shell)

**Lighting strike EIA** 10K amps - 6 times

**EMI Shielding EIA** - 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB

**IP Rating** 68

