

Mechanical characteristics

cable group

interface dimensions acc. to assembly code

Components

centre contact
outer contact
crimp ferrule
insulator

Environmental

RoHS compliant

Mechanische Eigenschaften

Kabelgruppe

Steckgesicht nach Montageanleitung

Bauteile

Innenkontakt
Außenkontakt
Crimprohr
Isolierung

Umgebung

RoHS konform

(b) G 7: KX 22A; KX 3B; RG-174/U; RG-188A/U; RG-316/U

IEC 60169-15
C0703



Materials / Material

CuBe2
CuZn39Pb3
SF Cu w
PTFE

Finish / Oberfläche

(c) Cu1Ni2Au1.27
NiP-Au
Cu1Ni5Au0.2

2002/95/EC (c)

c	19564	16.01.08	MA	1998	Datum/date	Name/name	Werkstoff/ material
	b	10937	BA	gez./drawn	13.05.	HR	
	a	9127	HR	gepr./appr.	13.05.98	BJ	Oberfläche/ finish
				Norm/stand.			
				Maßstab/scale	Benennung/title		
				5:1	SMA Straight Jack SMA-Kabelbuchse		
				untol. Maße/ dim. without tolerances according to	Untert./doc.type	Zeichnungsnr./drawing no.	
					K	J01151A0051	 Maße/dimensions: mm
					Ersatz für/ replaces		Original: DIN A4