

Pushbutton with connector M12, Ø 22 mm, stainless steel 316L, Series 82, Ø 25 mm, flush, Silver, IP65, IP67, Connector M12

82-6657.1000



<https://eao.com/p/24d8d142>

Your product:

---



82-6657.1000

Pushbutton with connector M12, Ø 22 mm, stainless steel 316L, Series 82, Ø 25 mm, flush, Silver, IP65, IP67, Connector M12

#### PRODUCT RANGE

**HMI function:** Pushbutton

**Series:** Series 82

#### FRONT

**Front dimension:** Ø 25 mm

**Front bezel colour:** Silver

**Front bezel material:** Stainless steel 316L

#### MOUNTING

**Design:** flush

**Mounting cut-out:** Ø 22 mm

#### OPERATING-/INDICATION PART

**Lens illumination:** non illuminative

**Lens colour:** Silver

**Lens shape:** flush

**Lens material:** Stainless steel 316L

#### ELECTRICAL CHARACTERISTICS

**Electrical lifetime:** 50 000 cycles of operation  
**Switching rating:** 35 V AC/DC @ 0,5 A

### MECHANICAL CHARACTERISTIC

**Tightening torque:** Fixing nut 0.5 Nm min. ... 1.2 Nm max., Screw terminal 0.1 Nm  
**Contact material:** Silver  
**Terminal:** Connector M12  
**Switching action:** Momentary  
**Switching system:** Snap-action switching element  
**Total weight:** 0.043 kg

### AMBIENT CONDITION

**IP front protection:** IP65, IP67  
**Operating temperature:** - 30 °C ... + 70 °C  
**Storage temperature:** - 40 °C ... + 80 °C

### OTHER

**max. number of switching elements:** 1  
**Housing colour:** Silver  
**Housing material:** Stainless steel  
**Gehäuse Grösse:** 19 mm  
**Symbol:** no symbol  
**Article number:** 82-6657.1000