

Pushbutton with connector M12, Ø 22 mm, stainless steel 316L, Series 82, Ø 25 mm, flush, Silver, IP65, IP67, Connector M12

82-6657.2000

<https://eao.com/p/d16738f2>

Your product:



82-6657.2000

Pushbutton with connector M12, Ø 22 mm, stainless steel 316L, Series 82, Ø 25 mm, flush, Silver, IP65, IP67, Connector M12

PRODUCT RANGE

HMI function: Pushbutton

Series: Series 82

FRONT

Front dimension: Ø 25 mm

Front bezel colour: Silver

Front bezel material: Stainless steel 316L

MOUNTING

Design: flush

Mounting cut-out: Ø 22 mm

OPERATING-/INDICATION PART

Lens illumination: non illuminative

Lens colour: Silver

Lens shape: flush

Lens material: Stainless steel 316L

ELECTRICAL CHARACTERISTICS

Electrical lifetime: 50 000 cycles of operation
Switching rating: 35 V AC/DC @ 0,5 A

MECHANICAL CHARACTERISTIC

Tightening torque: Fixing nut 0.5 Nm min. ... 1.2 Nm max., Screw terminal 0.1 Nm
Contact material: Silver
Terminal: Connector M12
Switching action: Maintained
Switching system: Snap-action switching element
Total weight: 0.043 kg

AMBIENT CONDITION

IP front protection: IP65, IP67
Operating temperature: - 30 °C ... + 70 °C
Storage temperature: - 40 °C ... + 80 °C

OTHER

max. number of switching elements: 1
Housing colour: Silver
Housing material: Stainless steel
Gehäuse Grösse: 19 mm
Symbol: no symbol
Article number: 82-6657.2000